



	Nominal Voltage	Figure	Dimensions Inches				
			A	B	E	I	P
1	2400	1	10.87	3	7	***	****
2	2400	3	10.87	3	7	***	1.25
3	2400	3	15.9	3	12	***	1.25
4	2400	1	15.9	3	12	***	***
5	2400	1	10.9	3	7	***	***
6	2400	3	10.9	3	7	***	1.25
7	2400	3	15.9	3	12	***	***
8	2400	2	10.9	3	7	3.56	***
9	2400	4	10.9	3	7	3.56	1.25
10	2400	4	15.9	3	12	3.31	1.25
11	2400	2	15.9	3	12	3.31	***
12	2400	2	10.9	3	7	3.56	***
13	2400	4	10.9	3	7	3.56	1.25
14	2400	4	15.9	3	12	3.31	1.25
15	4800	3	15.9	3	12		1.25
16	4800	1	15.9	3	12	***	***
17	4800	3	15.9	3	12		1.25
18	4800	4	15.9	3	12	3.31	1.25
19	4800	2	15.9	3	12	3.31	***
20	4800	4	15.9	3	12	3.31	1.25
21	7200	3	15.9	3	12	***	1.25
22	7200	4	15.9	3	12	3.31	1.25

Non-indicating for use in Class 1 Div II areas.

TITLE HERMETICALLY SEALED HIGH VOLTAGE POWER FUSES	CATALOG NO MR-2	REV
		DATE 4/4/06
		SHEET 1 of 1